

Simple, reliable and fast The Hensel Box with plug-in terminals





The Hensel Box


with plug-in terminals and mounting supports

Product features:

- 2x Wago 221-500 mounting supports
- 5x Wago 221-413 3-wire compact splicing connectors
- pre-assembled DIN rail
- offering all benefits of the new DK cable junction boxes with degree of proctection IP 66



Mounting benefit 1: Terminal levers can also be operated without difficulty when assembled.



Mounting benefit 2: The terminal can be positioned variably on the pre-assembled DIN rail.



DK 0404 W

0.75-4 mm², Cu 3~

- with 2x Wago 221-500 mounting supports and 5x Wago 221-413 3-wire compact splicing connectors
- per splice connector 3 x 0.14 4 mm² f, 3 x 0.2 4 mm² sol / s
- with elastic membranes, which can be removed for cable entry via cable glands, sealing range 9.0-17.0 mm
- with one cable entry in the bottom, sealing range Ø 6.0-15.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

rated insulation voltage	$U_i = 450 \text{ V a.c./d.c.}$
rated current	32 A
material	PP (polypropylene)



[2xM20/25] 2x Ø9-17 mm 2x Ø9-17 mm 2xM20/25 2xM20/25 0 1xM20/25

Product benefits DK cable junction boxes



cable entry via integrated elastic membranes



alternatively, for cable entry via cable glands elastic membranes and extension ring can easily be removed



cable entry through the bottom of the box via integrated elastic membrane



retaining strap prevents the lid from falling or losing



external brackets for fastening are always included

Gustav Hensel GmbH & Co. KG **Industrial Electrical Power Distribution Systems**

Gustav-Hensel-Straße 6 D-57368 Lennestadt, Germany P.O. Box 1461 D-57344 Lennestadt, Germany

Phone: +49 (0)27 23/6 09-0 Fax: +49 (0)27 23/6 00 52 E-Mail: info@hensel-electric.de www.hensel-electric.de